

◆ ZJQ5125



Drill press	
Max Drilling Diameter(mm)	Φ25mm(1")
Motor Power	1.5HP
Chuck Capacity(mm)	5-20
Spindle Travel(mm)	85
Class Of Speed	12
Speed 50/60HZ	280-2380/340-2860R.P.M
Spindle Taper	MT3

Drill press	
Max distance from spindle axis to surface of column(mm)	176
Max distance from spindle end to surface of table(mm)	685
Max distance from spindle end to surface of base(mm)	1175
Swing(mm)	352
Table Size(mm)	290*290

Drill press	
Base Size(mm)	460*272
Column Diameter(mm)	Φ80
Height(mm)	1600
Net Weight/Gross Weight(kg)	59/62
Packing Size(mm)	1140*490*270



◆ ZJQ5132



Drill press	
Max Drilling Diameter(mm)	Φ32mm(1-1/4")
Motor Power	2HP
Chuck Capacity(mm)	5-20
Spindle Travel(mm)	120
Class Of Speed	12
Speed 50/60HZ	150-2450/180-2940R.P.M
Spindle Taper	MT4

Drill press	
Max distance from spindle axis to surface of column(mm)	220
Max distance from spindle end to surface of table(mm)	700
Max distance from spindle end to surface of base(mm)	1225
Swing(mm)	440
Table Size(mm)	360*360

Drill press	
Base Size(mm)	470*360
Column Diameter(mm)	Φ92
Height(mm)	1710
Net Weight/Gross Weight(kg)	98/103
Packing Size(mm)	1415*645*295

◆ ZJQ4116B



Drill press	
Max Drilling Diameter(mm)	Φ16mm(5/8")
Motor Power	1HP
Chuck Capacity(mm)	3-16
Spindle Travel(mm)	60
Class Of Speed	12
Speed 50/60HZ	300-2550/360-3060R.P.M.
Spindle Taper	MT2

Drill press	
Max distance from spindle axis to surface of column(mm)	155
Max distance from spindle end to surface of table(mm)	490
Max distance from spindle end to surface of base(mm)	610
Swing(mm)	310
Table Size(mm)	Φ260

Drill press	
Base Size(mm)	420*250
Column Diameter(mm)	Φ58
Height(mm)	900/950
Net Weight/Gross Weight(kg)	31/33
Packing Size(mm)	770*450*260



◆ ZJQ4120



Drill press	
Max Drilling Diameter(mm)	Φ20mm(3/4")
Motor Power	1.5HP
Chuck Capacity(mm)	5-20
Spindle Travel(mm)	80
Class Of Speed	16
Speed 50/60HZ	180-2770/220-3320R.P.M
Spindle Taper	MT2


Drill press	
Max distance from spindle axis to surface of column(mm)	162.5
Max distance from spindle end to surface of table(mm)	420
Max distance from spindle end to surface of base(mm)	630
Swing(mm)	325
Table Size(mm)	250*250

Drill press	
Base Size(mm)	420*250
Column Diameter(mm)	Φ72
Height(mm)	980
Net Weight/Gross Weight(kg)	40/42
Packing Size(mm)	770*450*260

Drilling Machine & Drillpress Vice



Model	ZI4113	ZJQ4116K	ZJQ4116B	ZJQ4120	ZJQ5125	ZJQ5132
Drilling Cap. (mm)	13mm(1/2")	16mm(5/8")		20mm(3/4")	25mm(1")	32mm(1-1/4")
Motor Power	250/350W	375W/450W		750W	900W	1100W/1500W
Spindle Travel (mm)	50	65		85	85	120
Class of Speed	5	5	12	16	12	
Spindle Taper	B16	B16	MT#2		MT#3	MT#4
Swing (mm)	210	260	310	325	360	450
Table Size (mm)	160x190	250	260	250x250	290x290	360x360
Base Size (mm)	290x190	340x210	420x250	420x250	460x272	470x360
Column Dia. (mm)	∅ 46	∅ 58		∅ 70-72	∅ 80	∅ 92
Height (mm)	580	840	900	1000	1600	1710
N.W/G.W (kg)	19/20	34/36	40/42	51/53	80/84	130/138
Packing Size (mm)	435x340x320	680x430x265	780x450x280	780x450x280	1140x500x3000	1430x670x330



Model	Size	Width of JAW(mm)	Qty/Ctn	Weight/Ctn(kg)	Ctn Size(cm)
9704	100mm	100	1	10.5	29x29x17
9705	125mm	125	1	14.5	30x30x20
9706	150mm	150	1	17.5	32x32x20



American Type Drill Press Vice				
Size	Jaw Width	Jaw Opening	Packing Size	N.W
2.5"	63mm	50mm	335x290x29/20pcs	28kg
3"	75mm	60mm	330x335x230/10pcs	18kg
4"	100mm	80mm	380x340x255/10pcs	25kg
5"	125mm	100mm	380x300x230/5pcs	18.5kg
6"	150mm	120mm	380x320x280/5pcs	28kg

Drilling Machine (Heavy Duty)



Model	LG-16	LG-25B	LG-25A
Max Drilling Capacity	Φ16mm	Φ20mm	Φ25mm
Spindle Taper	MT2	MT3	
Spindle Travel	100mm	120mm	140mm
Spindle Speed r.p.m	240-2840(50Hz) 290-3440(60Hz)	230-1910(50Hz) 270-2290(60Hz)	
Number of Speed	9		
Swing	Φ360mm	Φ460mm	Φ460mm
Column Diameter	Φ80mm	Φ92mm	Φ102mm
Table Diameter	Φ320mm	Φ400mm	Φ420mm
Base Size	335×580mm	335×580mm	380×600mm
Distance from Spindle to Table	450mm	720mm	630mm
Distance from Spindle to Base	620mm	920mm	930mm
Motor HP	1HP	2HP	
Overall Height	1070mm	1500mm	1540mm
Weight	90Kg	140Kg	190Kg



HOLE CUTTING DRILL



Model No.	HC127
Power input	1100 Watt
Voltage	230V / 50Hz, 110V / 60Hz
No load speed	130 RPM
Max. Cutting Capacity	127mm
Pipe Mounting Capacity	32 mm - 203 mm
Drill Chuck Capacity	1mm-16 mm
Over load protection	With
Soft start	Without
Overall Dimensions (LxWxH)	319 mm X 270 mm X 302 mm
Net weight	14.5kgs (31.9Lbs) not include side Handle



: Model	ZS4116B
: Feature	Drilling & Tapping
: Drill/Tapping Capacity	16mm/M12
: Chuck Capacity	3~16mm
: Column Diameter	70mm
: Spindle Travel	100mm
: Swing	410mm
: Max. Distance spindle to table	320mm
: Max. Distance spindle to base	575mm
: Spindle Taper	MT2
: Speed Range	300~2680RPM
: No. of Speed	5
: Table Size	283X248mm
: Base Size	520x345mm
: Overall Height	1040mm
: Motor	380V/750W/50Hz
: Weight	113KG
: Packing Size	750x430x950mm